

# HVAC RNTL

**MODEL: OWC3612**  
**3 TON DELUXE PORTABLE**  
**WATER-COOLED AIR CONDITIONER**

## TECHNICAL SPECIFICATIONS

<b>COOLING CAPACITY</b>	<b>36,100 BTUH</b>
VOLTAGE	208-230V, 60Hz, 1PH
AMPS	12.0
TOTAL WATTS	2700
IN RUSH AMPS	100
PLUG TYPE	6-20P, LCDI
EER	13.4
COMPRESSOR	SCROLL
COMPRESSOR HP	3
COMPRESSOR LRA	83
EVAP CFM - HIGH	1200
EVAP MOTOR HP	1/3
CONDENSER WATER FLOW	
AT 60°F WATER IN	2.2 GPM
AT 85°F WATER IN	9 GPM
WATER LINE CONNECTIONS	
WATER IN	5/8 MF
WATER OUT	5/8 MF
DRAIN	3/8 MF
CONDENSATE REMOVAL	PUMP AUTOMATIC 20' VERTICAL LIFT
REFRIGERANT CHARGE	24 oz R-410A
HEIGHT	50-14 in
WIDTH	28-1/4 in
DEPTH	18 in
NET WEIGHT	275 lb

### SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air with 85°EWT and 105°LWT
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed
- OA CFM with free discharge
- OA Amps & Watts at 208 Volts

**COOLING AMBIENT**      **OPERATING RANGE 65° TO 105°**  
**NOT APPROVED FOR OUTDOOR USE**



**WATER COOLED**



# HVAC RNTL

## MODEL: OWC3612 3 TON DELUXE PORTABLE WATER-COOLED AIR CONDITIONER

### PRODUCT FEATURES

- OA SOLID STATE ELECTRONIC CONTROLLER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA INTERNAL CONDENSATE PUMP WITH OVERFLOW ALERT
- OA WATER REGULATING VALVE
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTER



### ACCESSORIES

