

TECHNICAL SPECIFICATIONS

COOLING CAPACITY	60,100 BTUH
VOLTAGE	208-230V, 60Hz, 3PH
AMPS	16.5
TOTAL WATTS	5000
IN RUSH AMPS	149
PLUG TYPE	L15-30P
EER	12.0
COMPRESSOR	SCROLL
COMPRESSOR HP	5
COMPRESSOR LRA	137
EVAP CFM - HIGH	1950
EVAP MOTOR HP	1
CONDENSER WATER FLOW	
AT 60°F WATER IN	3.8 GPM
AT 85°F WATER IN	15 GPM
WATER LINE CONNECTIONS	
WATER IN	5/8 MF
WATER OUT	5/8 MF
DRAIN	3/8 MF
CONDENSATE REMOVAL	PUMP AUTOMATIC 20' VERTICAL LIFT
REFRIGERANT CHARGE	52 oz R-410A
HEIGHT	51-1/2 in
WIDTH	27 in
DEPTH	29 in
NET WEIGHT	375 lb

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air with 85°EWT and 105°LWT
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed
- OA CFM with free discharge
- OA Amps & Watts at 208 Volts

COOLING AMBIENT **OPERATING RANGE 65° TO 105°**
NOT APPROVED FOR OUTDOOR USE



WATER COOLED



PRODUCT FEATURES

- OA SOLID STATE ELECTRONIC CONTROLLER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA INTERNAL CONDENSATE PUMP WITH OVERFLOW ALERT
- OA WATER REGULATING VALVE
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTER
- OA THREE PHASE MONITOR



HANDLES

HOSE STRAP

CONTROL BOX
ACCESS

RECESSED
FITTINGS

CONDENSATE
PUMP ACCESS

KICK PLATE

OWC60 REAR DETAIL

- Rear Handles and Kickplate for Mobility
- Power Cord Storage
- Manual Reset High Pressure Cut-out Switch
- Recessed Water Connections
 - ° Water In - 5/8 Flare
 - ° Water Out - 5/8 Flare
 - ° Drain - 3/8 Flare

ACCESSORIES

